SUPERSCOPE

CS-200S Rechargeable Portable AC/DC Stereo Cassette Recorder

With 2 External Speakers and Large Garrying Gase

Now — enjoy the clarity and spaciousness of full-fidelity stereo sound — wherever you go. Superscope's CS-200S brings you all that and more. Truly portable (AC/DC powered) it has a handsome flexible carrying case and two external speakers, plus additional built-in speaker.

Enjoy the CS-200S at home, in the living room, or as a "second stereo" in bedroom or den. Take it to that weekend cabin or use it in the camper. Entertain the children while traveling in your car. Or, use it with your present system as a stereo cassette deck.

How can we do it? Easy. Superscope has years of experience bringing you the world's finest audio equipment — Sony tape recorders and Marantz stereo components. Superscope products continue this tradition of excellence.

Superscope's CS-200S: when only the best in portable stereo will do.





SUPERSCOPE

SUPERSCOPE

CS-200S Rechargeable Portable AC/DC Stereo Cassette Recorder With 2 External Speakers and Large Carrying Case



- **Rechargeable Feature** automatically recharges batteries when using AC power
- Mechanical Auto-Stop at end-of-tape
- Auto Record Level
- VU/Battery Meter combines accurate recording level monitoring and visual indication of battery strength
- Two Built-In Mics for high quality stereo recording.
- Tape Select Switch allows for use of new Chromium Dioxide cassettes.
- Two External Speakers for full stereo fidelity
- **Tone Control**
- **Stereo Balance Control**
- Mono Compatibility
- Three-Digit Resettable Tape Counter



- Speaker Earphone Monitor
- Mic/Remote Input
- Two Auxiliary Inputs

Supplied Accessories:

- AC Power Cord
- Size "C" Batteries (4)
- Two Audio Patch Cords
- Flexible Carrying Case for all three pieces
- Head Cleaning Sticks

Recommended Accessories:

CBC-200 Carrying Case

Specifications:

Power Requirements: AC: 120 V., 10 Watts, 60 Hz DC: 6 V. Battery size & quantity: "C" Size Batteries (4) Tape Speed: 17/8 ips **Recording System: Cassette** Rewind & Fast Forward Time: 75 Sec./C-60 Cassette Frequency Response: 60 Hz-12 kHz (±6 dB, CrO₂ Tape, Line Outputs) Signal to Noise Ratio: -45 dB (CrO₂ Tape) 2 Inputs 1. Auxiliary Plug type: RCA Type Pin Impedance: 100k Ohms Input sensitivity: 0.08 V 2. Microphone Plug type: Mini Impedance: Low Input sensitivity: -72 dB Speaker Complement: Built-In 4" Speaker/Two External 5" Speakers Bias Frequency: 80 kHz Power Output: 1.0 Watts Continuous Power Wow & Flutter: 0.3% Number & Type of Motor: One DC, Governor Controlled 4 Outputs 1. Line (one for each channel) Impedance: 5k Ohms Output level: 0.775V (at 0 VU) 2. Lid speakers (one for each channel) Impedance: 8 Ohms Output power: 1.5 Watts (music power) 3. Stereo Headphone Jack Impedance: 270 Ohms (Use 8 Ohms Stereo Headphone) 4. Earphone/Monitor Output Impedance: 8 Ohms Output Level: 0-2.9 V Dimensions (WHD): 6-11/64"x3-1/32"x10-53/64" One External Speaker: 6-11/64"x3-21/32"x10-53/64" Unit weight: 5.3 Lbs. 2.2 Lbs. (one external speaker) SUPERSCOPE WARRANTY Superscope, Inc., guarantees the original registered owner that all parts are free from operating defects for one year from purchase date. Products are repaired or replaced free of charge, provid-



You never heard it so good®

8150 Vineland Ave. . Sun Valley, Calif. 91352

ing you bought it in the U.S.A. from an authorized dealer. Naturally, the serial number cannot be altered or removed. We suggest you keep the original carton. Because if you ship the product for repairs in the original package fully prepaid within the U.S.A., it will be returned to you prepaid within the U.S.A.